

**A 16 OR**



**A 16 OR**



**A 22 OR**



**A16-A22** are traditional style horizontal log splitters, robust and practical thanks to their construction on a non-deformable beam, available in many versions and always with double speed and 4-split wedge. These models can be built bespoke to suit your individual requirements.

**A16-A22** sont les traditionnelles fendeuses de bûches horizontales, robustes et pratiques grâce à la construction sur une poutre non déformable, disponibles dans des nombreuses versions et toujours avec double vitesse et coin à 4 fentes.

## TECNICAL DATES / FICHE TECHNIQUE

ART												
		TON	KG	cm	cm	BAR	LITERS	L/MINUTE	SPEED	SPEED	RETURN	HP
							OIL		cm/s	cm/s	cm/s	
11231	<b>A16 OR 650 C</b> Tractor PTO	16	280	70	190X80X85	220	35	40	9	24	14	40
11224	<b>A16 OR 650 ET ROAD</b> 380 Volt	16	330	70	210X120X115	220	35	20	4,5	12	7	5,5
11242	<b>A16 OR 650 PI</b> Tractor hydraulics	16	200	70	190X80X85	220	35	/	/	/	/	/
11255	<b>A16 OR 650 SB ROAD</b> Fuel Engine / Benz. ✓	16	330	70	210X120X115	220	35	13	2,7	7,5	4,2	6
11281	<b>A16 OR 1060 C</b> Tractor PTO	16	340	110	275X80X85	220	35	40	9	24	14	40
11274	<b>A16 OR 1060 ET ROAD</b> 380 Volt	16	390	110	295X120X115	220	35	20	4,5	12	7	5,5
11292	<b>A16 OR 1060 PI</b> Tractor hydraulics	16	265	110	275X80X85	220	35	/	/	/	/	/
11305	<b>A16 OR 1060 SB ROAD</b> Fuel Engine / Benz. ✓	16	390	110	295X120X115	220	35	32	6,5	19	11	6
11331	<b>A22 OR 1060 C</b> Tractor PTO	22	460	110	290X90X95	230	45	70	15	36	24	85

## OPTIONALS

ART			ART		
<b>OPA220R5</b>	Caricamento idraulico laterale	(solo 1050)	<b>OPA160R3</b>	Ruote e traino su strada	(asse rigido, solo su strada privata)
	Lateral hydraulic loading	(only 1050)		Wheels and drawbar for road use	(rigid axle, only for private road)
<b>OPA160R4</b>	Assale molleggiato	(solo per road)			
	Sprung axle	(road version only)			

**PER MISURE EXTRA CONTATTARE LA SEDE  
FOR SPECIAL SIZES CONTACT THE FACTORY**



Via Galimberti, 64 • 12030 MANTA (CN) ITALY  
Tel. 0039.0175.289070 / 0039.0175.289391 • Fax 0039.0175.289016 • info@balfor.it

www.balfor.it